

BOLT TENSIONER ACCESSORIES | HOSES, COUPLERS & HOSE REEL



Hose lengths up to 984 feet

Supplied with quick connect couplings

Design pressure 21750 psi with 3:1 safety factor

XHR1 HOSE REEL

- ▶ Designed for sub-sea main line hose connection between the pump and the first tensioner
- ▶ Accommodates up to 984 ft of XHC bolt tensioner hydraulic hose
- ▶ Complete with quick connect couplings, integrated brake and a spring loaded locking bolt



Dimensions
Length 31.5" x Width 23.6" x Height 34.2"

Model number	Description	Weight (lbs)
XHC1.5B	Link hose complete with quick connect couplings, length 5 ft	2.2
XHC3B	Link hose complete with quick connect couplings, length 10 ft	3.7
XHC5B	Mainline hose complete with quick connect couplings, length 16.5 ft	5.7
XHC10B	Mainline hose complete with quick connect couplings, length 33 ft	9.9
XHC25B	Mainline hose complete with quick connect couplings, length 82 ft	18.7
XHC50B	Mainline hose complete with quick connect couplings, length 164 ft	37.3
XHC100B	Mainline hose complete with quick connect couplings, length 330 ft	74.1
XHC150B	Mainline hose complete with quick connect couplings, length 492 ft	111.6
XHC200B	Mainline hose complete with quick connect couplings, length 656 ft	147.7
XHC250B	Mainline hose complete with quick connect couplings, length 820 ft	184.5
XHC300B	Mainline hose complete with quick connect couplings, length 984 ft	221.3
XHR1	Hose reel, suitable for up to 984 feet of XHC high pressure hose	61.7
STFC4	Female coupling	0.9
STMC4	Male coupling	0.4
STN1P2	1/8" x 1/4" BSP nipple for current model STS1 only	0.9
STN1P4-C	1/4" BSP nipple with cone seat seal (current design - not for STS1)	1.5

Note: XHC high pressure bolt tensioner hoses up to 49 ft in length are supplied with a clear protective sleeve.