

HYDRAULIC OIL



Premium grade hydraulic oil

High viscosity index

Supplied in a choice of 1, 5 or 25 litre containers

- ▶ Effective and reliable lubricant
- ▶ Foaming resistance
- ▶ Provides optimum performance in all high pressure applications
- ▶ Specially formulated for use with all Hi-Force hydraulic tools

Model number	Contents (litres)
HFO15-1	1
HFO15-5	5
HFO15-25	25
HFO46-1	1
HFO46-5	5
HFO46-25	25

OIL TYPE RECOMMENDATION

Product	Oil Type	
	HFO15	HFO46
ACP	•	✓
AHP/AHP-CR/AHP2/ AHP2-CR/ATDP	•	✓
AHP11	•	✓
BC	•	✓
BPP	•	✓
CH	•	✓
Controlled Manifolds	✓	✓
Couplers & Fittings	✓	✓
CT	✓	•
Digital Gauge	✓	✓
DNS	•	✓
Gauge/Blocks	✓	✓
HAP	•	✓
HAS	•	✓
HBW	•	✓
HCC	•	✓
HCH	•	✓
HDA	•	✓
HEP1	•	✓
HEP103	•	✓
HEP2/HEP3/HEP5	•	✓
HFA	•	✓
HFG	•	✓
HFL	•	✓
HFS-H	•	✓
HFV42	✓	•
HFV66	✓	•

Product	Oil Type	
	HFO15	HFO46
HGG	•	✓
HHA	•	✓
HHP	•	✓
HHR	•	✓
HHS	•	✓
HKP	✓	•
HLS	•	✓
HMJ	•	✓
HMNS	✓	•
Hoses	✓	✓
HP(All)	✓	•
HP-FP	✓	•
HPC	•	✓
HPF	•	✓
HPP	•	✓
HPR/HBR	✓	•
HPS	•	✓
HPT	✓	✓
HPX	✓	•
HPV152	✓	•
HRA	•	✓
HSG	•	✓
HSP	•	✓
HSS	•	✓
HSWC	✓	•
HTN	•	✓
HTWP	•	✓
HTWR1	•	✓

Product	Oil Type	
	HFO15	HFO46
HVL	•	✓
HWRC	•	✓
JAH	✓	•
JAS	✓	•
JCS/JCH	✓	✓
Manifolds	✓	✓
MHP	✓	•
NS	•	✓
PB	✓	•
PKC	•	✓
PKS	•	✓
PMV2	•	✓
PMV3/PMV3L	•	✓
PMV4/PMV4L	•	✓
RMV3/RMV3L	•	✓
RMV4/RMV4L	•	✓
SBT	•	✓
SC	✓	•
SCP	✓	•
SPP	✓	•
STS	•	✓
STU	•	✓
Toughlift	•	✓
TPA	•	✓
TPE	•	✓

Note: ✓ Recommended and factory fitted grade
• Acceptable alternative