

PRESSURE GAUGES & GAUGE MOUNTING BLOCKS



Clear precise dual scale readings

Manufactured to EN837-1

+/-1% full scale accuracy

GAUGES

- ▶ Choice of dry or glycerin filled models available
- ▶ Recommended for use within all hydraulic systems to monitor hydraulic pressure
- ▶ Dual scale reading on all models
- ▶ Gauges scaled to match high tonnage cylinders available on request
- ▶ Individual gauge calibration certificates available at extra cost on request

Model number	Gauge diameter (in)	Gauge type	Reading inner scale	Reading outer scale	Inlet thread	Compatible Hi-Force cylinders	Weight (lbs)
HG63G	2.48	glycerin	0-700 bar	0-10000 psi	1/4"-18 NPT	All models	0.4
HG1	3.94	dry	0-700 bar	0-10000 psi	1/2"-14 NPT	All models	2.0
HG1G	3.94	glycerin	0-700 bar	0-10000 psi	1/2"-14 NPT	All models	2.2
HG2	5.91	dry	0-700 bar	0-10000 psi	1/2"-14 NPT	All models	3.5
HG2G	5.91	glycerin	0-700 bar	0-10000 psi	1/2"-14 NPT	All models	3.7

GAUGE MOUNTING BLOCKS

- ▶ For easy "inline" connection of the selected pressure gauge to the hydraulic system

Model number	Length	Dimensions (in) Width	Height	Gauge thread	Inlet thread	Outlet thread	Weight (lbs)
HGA1	2.96	1.26	1.26	1/2"-14 NPT	3/8"-18 NPT male	3/8"-18 NPT female	0.6
HGA2	6.3	1.26	1.26	1/2"-14 NPT	3/8"-18 NPT male	3/8"-18 NPT female	1.9
HGA1-25	2.96	1.26	1.26	1/4"-18 NPT	3/8"-18 NPT male	3/8"-18 NPT female	0.7
HGA2-25	6.3	1.26	1.26	1/4"-18 NPT	3/8"-18 NPT male	3/8"-18 NPT female	2.0
AGA1-25	2.96	1.26	1.97	1/4"-18 NPT	3/8"-18 NPT male	3/8"-18 NPT female	1.2